



Karvekrete

PRODUCT DATA

Concrete Finishes

LIFETIME FLOORS Karvekrete

Description

Karvekrete is a decorative, integrally colored plaster finish for interior and exterior use. It creates an “old-world” look and emulates antique and textured stones.

Karvekrete is a dry powdered formula mixed simply with water.

Yield

3/8” thick 17 sf, per bag.

Packaging

50 lb bag

Color

Out of bag mix cures to a white color. Integral color can be added to Karvekrete to create a wide range of colorful pieces.

Shelf Life

18 months when properly stored

Storage

Store in unopened packaging in clean dry area protected from direct sunlight at 50-90 degrees F.

Features

- Creates artistic “old world” look
- Can create both smooth and distressed finishes
- Variety of color options available

Where to Use

Karvekrete is used as a plaster for walls and special decorative features. It is recommended for both interior and exterior environments and for commercial and residential. If used on ceilings please use with caution.

Application

How to Apply

Surface Preparation

Make sure surface is clean and cured. Dampen surface before you begin application.

Mixing

Mix 1 bag of Karvekrete mix with water until Mortar consistency. Mix thoroughly. Work time is approximately 30 minutes.

Primer

Use cement board or brown coat (spec mix). Expanded metal lath can also be used.

Application

Use a trowel to spread on Karvekrete mix. Thickness should be about 3/8” – 3/4”. Spread evenly over entire space in fluid motions feathering from bottom corner up.

Use tuck point to carve out decorative finish and cracks.

Benefits

- Simply mix the bag and water
- One application process
- Used for both Internally and externally

Sealing

Let Karvekrete to dry for 72 hours. Consult your local LifeTime Floors representative for best used methods.

For Best Performance

- Materials must be stored and mixed at temperatures of 65-80°F (18-26°C).
- Never apply LTF Karvekrete mix below 55°F and never allow product to freeze.
- Do not apply for exterior use if rain is expected within 24 hours
- Be sure to use all the provided polymer resins. Scrape hardener from container.
- Do not turn mixing vessels upside down to drain on flooring surface.
- Keep unfinished wall surface clean.
- Do not track dirt, grease, and other contaminants onto unfinished walls
- Good ventilation must be provided during application.
- Always obtain, read and observe Manufacturer’s Safety Data Sheet before handling.
- This application is not designed to bridge cracks, working joints, dynamic cracks or expansion joints.



Health and Safety

LTF Karvekrete

Caution

Risks

Eye irritant. Skin irritant. Causes burns. Lung irritant. May cause delayed lung injury.

Precautions

KEEP OUT OF THE REACH OF CHILDREN. Avoid contact with eyes. Wear suitable protective eyewear. Avoid prolonged or repeated contact with skin. Wear suitable gloves. Wear suitable protective clothing. Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Wash soiled clothing before reuse.

First Aid

Wash exposed skin with soap and water. Flush eyes with large quantities of water. If breathing is difficult, move person to fresh air.

Proposition 65

This product contains materials listed by the state of California as known to cause cancer, birth defects, or reproductive harm.

VOC Content

0lbs/gal or 0 g/L

Waste Disposal Method

This product when discarded or disposed of is not listed as a hazardous waste in federal regulations. Dispose of in a landfill in accordance with local regulations. For additional information on personal protective equipment, first aid, and emergency procedures, refer to the product Material Safety Data Sheet (MSDS) on the job site or contact the company at the address or phone numbers given on the bottom of the first page.

**For medical emergencies only,
call Chem Trec (1-800-424-9300)**

LIMITED WARRANTY NOTICE: Every reasonable effort is made to apply LifeTime Floors KarveKrete exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, LifeTime Floors LLC MAKES NO WARRANTY OR GUARANTEE- EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and LifeTime Floors LLC shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the LifeTime Floors LLC Technical Manager.

This information and all further technical advice are based on LifeTime Floors LLC present knowledge and experience. However, LifeTime Floors LLC assumes no liability for providing such information and advice indulging the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, LifeTime Floors LLC disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR OR MERCHANTABILITY. LIFETIME FLOORS LLC SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. LifeTime Floors LLC reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

For professional us only. Not for sale to or use y the general public.