



# Resurfacer

PRODUCT DATA

Concrete Finishes

## LTF Resurfacer

### Description

LifeTime Floors (LTF) Resurfacer is the preferred material for spray textures and exterior applications. It is a two-part polymer-modified cementitious coating, consisting of a unique rubber-like polymer liquid and a cement aggregate blend. The material is applied in multiple coats at a typical thickness of 3/32 inch. It can be applied over almost any clean, sound surface including concrete, cement block, tile, metal and wood.

### Yield

250-300 SF  
Average 2 coat application.

### Packaging

55

### Color

Gray or white

### Shelf Life

12 months when properly stored

### Storage

Store unopened packaging in a clean, dry area protected from sunlight at 50-90°F (10 to 32°).

### Features

Provides a tough water-retardant coating that substantially reduces water penetration, freeze-thaw scaling and concrete carbonation.

It is a "breathable" coating that releases normal entrapped vapor without loosening or blistering.

Thickness 1/16" – 1/8"

### Where to Use

#### APPLICATION

- Both in interior or exterior spaces
- Where textured surfaces are desired
- Over new or existing concrete
- Residential, commercial, municipal, and industrial

### How to Apply

#### Surface Preparation

- 1) Remove all loose decking material, paint or other coatings, spalled concrete, grease, oil, silicone coating, etc.
- 2) Grinding, shotblasting, pressure washing or scarifying are acceptable methods of surface prep.
- 3) Have control joint systems worked out to meet all stress points.
- 4) Repair any crack and control joints

### Mixing

Mix 2 gal of Multi Purpose Liquid per 55# bag of Resurfacer

- 1) Pour half of Multi Purpose liquid into clean 5 gallon bucket. In original pail, stir up any solid residue that settled on bottom and shake the bucket back and forth a few times.

### Benefits

Provides a sprayable cementitious coating for exterior and interior concrete surfaces.

Extraordinary adhesion and its ability to withstand prolonged pedestrian and vehicular traffic.

Tint Packs are available to achieve additional colors.

- 2) Optional – add tint pack at this point. Mix thoroughly
- 3) Pour both the stirred and shaken liquid into large mixing bucket. Mix with electric drill and gradually add the Concrete Resurfacer.
- 4) After mix is free of lumps, continue to mix at least 2 more minutes.
- 5) Apply Concrete Resurfacer immediately upon completion of mixing. Working time is about 30 minutes at 70 degrees F (21 -24 degrees C)

### Bond Coat

Concrete Resurfacer is applied to dry concrete.

Mix up to 2 gallons of Concrete Resurfacer liquid with 1bag. Do not dilute with water.

Apply bond coat immediately upon completion of mixing

Trowel on bond Coat. Cure time is about 2-4 hours or until no material comes up when you press your foot down on the deck.

A second coat should be applied in same manner as above, then broomed or textured.



## Textured, Stained, and sealed Finishes

Consult your local LTF representative for best methods used for the different types of finishes.

### For Best Performance

- Materials must be stored and mixed at temperatures of 65-80°F (18-26°C).
- Never apply LTF Thin Stamp Overlay mix below 55°F and never allow product to freeze.
- All curing agents, sealers and hardeners must be removed from concrete prior to primer application. Prep using mechanical shot blasting, grinding or power scarifying.
- Be sure to use all the provided polymer resins. Scrape hardener from container.
- Do not turn mixing vessels upside down to drain on flooring surface.
- Keep unfinished flooring surface clean.

- Do not track dirt, grease, and other contaminants onto unfinished flooring.
- Good ventilation must be provided during application.
- Always obtain, read and observe Manufacturer's Safety Data Sheet before handling.
- This application is not designed to bridge cracks, working joints, dynamic cracks or expansion joints.

### Health and Safety

LTF RESURFACER

#### Caution

#### Risks

Eye irritant. Skin irritant. Causes burns. Lung irritant. May cause delayed lung injury.

#### Precautions

KEEP OUT OF THE REACH OF CHILDREN. Avoid contact with eyes. Wear suitable protective eyewear. Avoid prolonged or repeated contact with skin. Wear suitable gloves. Wear suitable protective clothing. Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment. Wash soiled clothing before reuse.

### First Aid

Wash exposed skin with soap and water. Flush eyes with large quantities of water. If breathing is difficult, move person to fresh air.

### Proposition 65

This product contains materials listed by the state of California as known to cause cancer, birth defects, or reproductive harm.

### VOC Content

0lbs/gal or 0 g/L

### Waste Disposal Method

This product when discarded or disposed of is not listed as a hazardous waste in federal regulations. Dispose of in a landfill in accordance with local regulations. For additional information on personal protective equipment, first aid, and emergency procedures, refer to the product Material Safety Data Sheet (MSDS) on the job site or contact the company at the address or phone numbers given on the bottom of the first page.

**For medical emergencies only, call Chem Trec (1-800-424-9300)**

LIMITED WARRANTY NOTICE: Every reasonable effort is made to apply LTF Resurfacer exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, LTF LLC MAKES NO WARRANTY OR GUARANTEE< EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and LTF LLC shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the LTF LLC Technical Manager.

This information and all further technical advice are based on LTF LLC present knowledge and experience. However, LTF LLC assumes no liability for providing such information and advice indulging the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, LTF LLC disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR OR MERCHANTABILITY. LTF LLC SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. LTF LLC reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

For professional use only. Not for sale to or use y the general public.