



LIFETIME FLOORS
QuickTops ONE

Description

QUICKTOPS **ONE** pre-cast concrete mix is extensively researched and tested. QUICKTOPS **ONE** contains a proprietary blend of cements, polymers, fibers, and other admixtures to produce high quality, high strength, reduced porosity pre-cast concrete every time.

Yield

.46 cubic fee/bag or roughly 4 square feet at 1-1/2 thick.

Packaging

50 lb bags

Color

Out of the bag mix cures to an elegant buff color. Integral color can be added to QuickTops **ONE** to create a wide range of colorful pieces. Colored aggregates can also be blended in to add to the look of the polished product.

Shelf Life

18 months when properly stored.

Storage

Store in unopened packaging in a clean dry area protected from direct sunlight at 50-90 degrees F.

Features

Just mix with 1 gallon of water

Fast Setting mix design

Customized mix design

Polymer Modified

Fiber reinforced

Engineered mix design

Marble Based

Benefits

No need for additives or extra materials/extra steps

Quick turn a-round time/De-mold in approx. 3 hrs

Endless options available

Strong, durable, harder to scratch the surface.

Improved flexural strength, no need for steel reinforcing

Eliminates bug holes for tight finish

Decorative marble for ease of polishing

Where to Use

Commercial Residential and Restaurants

- 1) Countertops
- 2) Sinks
- 3) Exterior Sill Caps
- 4) Tiles
- 5) Pre-cast Interior
- 6) Pavers
- 7) Exterior Architectural Pre-cast
- 8) Natural Concrete

How to Use

Mix one 50 lb bag with one gallon of water. Add water to mixing tub then add powder while mixing with hand mortar mixer. Mix until completely blended and the mix has the consistency of pancake batter. Pour mix into forms starting at one corner and pouring from corner to corner to corner and then into the center until form is filled to level. Lightly tap all edges of the form to consolidate the material into the corners of the mold. Add material to achieve a level, full depth piece.

Curing

After product is placed in the form and properly consolidated and the mix has begun its initial set, add water to the surface and cover with poly sheeting.

Sealing

Consult your local QuickTops representative for best used methods.

For Best Performance

Store in a cool, dry place. Do not use material if packaging is damaged. Proper timing is essential for successful fabrication and installation of this product. Follow all the specified procedures at the recommended times. Make certain the most current versions of product data sheets and MSDS are being used: call Customer Service to verify the most current version. Proper application is the responsibility of the end user. Field visits for QuickTops personnel are for purpose of making technical recommendations only and not for supervising or providing quality control on jobsite.

QuickTops ONE

Just add 1 gallon of water to this polishable mix design to create custom "one of a kind" pieces.



Health and Safety

QUICKTOPS ONE

Caution

Risks

Eye Irritant. Skin irritant, Causes burns. Lung irritant. May cause delayed lung injury.

Precautions

KEEP OUT OF THE REACH OF CHILDREN. Avoid contact with eyes. Wear suitable protective eyewear. Avoid prolonged or repeated contact with skin. Wear suitable gloves. Wear suitable protective clothing. Do not breathe dust. In case of insufficient ventilation, wear suitable respiratory equipment. Wash soiled clothing before reuse.

First Aid

Wash exposed skin with soap and water. Flush eyes with large quantities of water. If breathing is difficult, move person to fresh air.

Waste Disposal Method

This product when discarded or disposed of is not listed as a hazardous waste in federal regulations. Dispose of in a landfill in accordance with local regulations. For additional information on personal protective equipment, first aid, and emergency procedures, refer to the product Material Safety Data Sheet (MSDS) on the job site or contact the company at the address or phone numbers given below.

Proposition 65

This product contains materials listed on the state of California as known to cause cancer, birth defects, or reproductive harm.

VOC Content

0 lbs/gal or 0g/L

**For medical emergencies only.
Call CHEMTRECS (1-800-424-9300)**

LIMITED WARRANTY NOTICE: Every reasonable effort is made to apply LifeTime Floors Quicktops ONE exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, LifeTime Floors LLC MAKES NO WARRANTY OR GUARANTEE< EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTIUCLAR PURPASE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and LifeTime Floors LLC shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the LifeTime Floors LLC Technical Manager.

This information and all further technical advice are based on LifeTime Floors LLC present knowledge and experience. However, LifeTime Floors LLC assumes no liability for providing such information and advice indulging the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, LifeTime Floors LLC disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR OR MERCHANTABILITY. LIFETIME FLOORS LLC SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. LifeTime Floors LLC reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

For professional us only. Not for sale to or use y the general public.